

**SPECIFICATION DATA SHEET**

- Type:** Natural Convective Panel Heater
(80% convective, 20% radiant)
- Element Type:** Stainless Steel with high efficiency, extended surface area, extruded aluminium heat exchange system.
- Design Voltage:** 220-240V, 50Hz
- Approvals:** AS/NZS60335.2.30:2004
- Degrees of Protection:** IP 24 Rating (suitable for use in bathroom)
- Safety Features:** Snap action bi metallic type fitted in air stream with safety cut out which operates if full outlet grill is blocked, also if half grill is blocked on either side.
Child lock standard on all models.
- Mounting:** Castor Wheel Set and Wall Mounting Bracket supplied.
- Operating Temperature:** At ambient temperature of 20°C the front panel of the heater operates at approximately 75°C. (Note; Australian standards allow a maximum of 120°C surface temperature on heaters of this type).
- Product Code:** ELEX ECO 1000 / 1500 / 2000 / 2400
- Control Type:** Push button timer (30 / 60 / 90 minute) and preset 21°C thermostat.
- Dimensions:** ELEX ECO 1000 – 420 x 440 x105mm
ELEX ECO 1500 – 580 x 440 x105mm
ELEX ECO 2000 – 740 x 440 x105mm
ELEX ECO 2400 – 1000 x 440 x105mm