

HEATSTRIP



INDOOR RADIANT HEATERS - THS SERIES

THS HEATSTRIP SPECIFICATION DATA SHEET

- Type:** Medium Intensity, Ceiling Mounted, Radiant Indoor Heaters
- Approvals:** Australian Standards 2250-2-30 (full test)
- Electrical Approval No:** Q97268
- Manufacture Location:** Melbourne Australia
- Element Type:** Stainless Steel with high efficiency, extended surface area, extruded aluminium heat exchange system.
- Design Voltage:** 230-240V, 50Hz a.c.
- Electrical Circuit:** Refer to Electrical Wattage.
- Paint Finish:** High temperature baked enamel paint.
- Connection Cord:** 3-coreflex – 400mm long
- Mounting System:** Ceiling mounting brackets are supplied as standard. Other options include – flush mounting, angle mounting, T-bar ceiling mounting, suspended mounting.
- Minimum Mounting Height:** 2.1 metres above floor level
(Refer installation instructions for recommended mounting height)

MODEL	WATTS	DIMENSIONS	IPX RATING	WEIGHT
THS 800	800	695 x 270 x 50	IPX-3	5.5kg
THS 1200	1200	955 x 270 x 50	IPX-3	7.0kg
THS 1800	1800	1405 x 270 x 50	IPX-3	10.0kg
THS 2400	2400	1820 x 270 x 50	IPX-3	12.5kg
THS 3600	3600	1820 x 400 x 50	IPX-3	18.0kg

Notes:

- These models have been given an International Protection (IPX) Ratings as defined by Australian Standards AS 1939-1991 'Classification of degrees of Protection against Liquids' provided by enclosures for electrical equipment.
- IPX-3 rating states these models are protected against spraying water at up to 60° from vertical.

